

## 4.8LPF / 1.28GPF

- ☐ **4782BOV** Bowl
- ☐ **4781BOVU** Unlined Tank

## PRODUCT SPECS

- High efficiency toilet
- 4.8Lpf / 1.28Gpf
- Elongated bowl with concealed skirted trapway
- Vitreous china
- 16½" Plus Height for greater comfort
- Soft white tank lever
- 12" (305mm) Rough-in
- 2" Fully glazed ball pass trapway
- 3" Flapper
- Siphon jet flush action
- Water surface: 9½" x 6⅝"  
(240mm x 170mm)
- Decorative soft white side caps included
- Smooth close toilet seat included

## DIMENSIONS

382mm W x 722mm D x 788mm H  
15" W x 28½" D x 31" H

## COMPLIANCE CERTIFICATIONS

Meets or exceeds the following:

- IAPMO cUPC
- ASME A112.19.2 / CSA B45.1
- ADA Guidelines & ANSI A117.1
- LEED Compliant
- CSA B651 barrier-free standard
- US EPA WaterSense
- MaP Tested 1000g

## SHIPPING

**Bowl:**

Cube	5.72
GW	88 lbs

**Tank:**

Cube	1.32
GW	30.4 lbs



**TO BE SPECIFIED**

Colour:

- Soft White

**NOTES:** The drawing below shows a rough-in at a minimum dimension of 305mm (12") from finished wall to C/L of outlet. Supply line not included with fixture and must be ordered separately.

Important: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ASME standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

Product is designed to comply with ADA / ANSI A117.1 and CSA B651 Barrier-Free Standard requirements, if installed according to the standard and local building codes. It is the responsibility of the installer to comply with this standard and local building codes prior to installation.

